

# SPIROVENT QUAD MAGNET

Hydraulic Separation plus  
Air/Dirt Elimination with Powerful Magnets

*The superior alternative to closely-spaced-Tees*



Industry-leading  
20-year guarantee

## SPIROVENT QUAD

Protect  
pumps, valves, boilers  
and heat exchangers  
from air, dirt and debris



Connections and coalescing  
medium are engineered to allow  
for the ultimate in hydraulic  
balance



Eliminates 100% of the free air,  
100% of the entrained air, and  
up to 99.6% of the dissolved air  
in the system



Separates dirt particles and  
ferrous material using powerful  
magnets around the flowpath

For information and availability:  
[www.spirotherm.com](http://www.spirotherm.com)

maximizing performance

# SPIROVENT QUAD MAGNET

## SPECIFICATIONS

- Brass body
- Brass vent head
- Non-ferrous float
- Viton seal
- Viton O-ring
- Engineered Spirotube® coalescing media
- Neodymium magnets
- 150 psig maximum working pressure
- 270°F maximum operating temperature
- Blowdown valve included



Model	NPT	VDX100FTM	VDX125FTM	VDX150FTM	VDX200FT*
	Sweat	VDX100SWM	VDX125SWM	VDX150SWM	VDX200SW*
	Pressfit	VDX100PFM	VDX125PFM	VDX150PFM	VDX200PF*
PS	Pipe Size	1"	1 1/4"	1 1/2"	2"
H2	inch	20-1/4	20-1/4	20-1/4	30-1/4
h2	inch	7-3/8	7-3/8	7-3/8	8-1/4
h3	inch	5-3/8	5-3/8	5-3/8	10-1/4
L	inch	8-5/8	8-5/8	8-5/8	10-1/8
D	inch	3-1/2	3-1/2	3-1/2	4
X	inch	4	4	4	4
Weight	lbs	13.2	14.3	15.4	26.4
Rec Flow	GPM	10	15	30	40

*dimensions for reference only* \*No Magnet

